ANGEL 8114

Protective textile glove with extremely durable PBI® fibre. In addition, the glove has a ceramic coating on exposed areas for increased abrasion resistance.





ANGEL Easy Beige



ANGEL Evo Beige



ANGEL Short Beige



ANGEL Long Beige

PRODUCT DESCRIPTION

ANGEL Flexi Beige 8114-11 ANGEL Evo Beige 8114-12 ANGEL Easy Beige 8114-13 ANGEL Long Beige 8114-14 ANGEL Short Beige 8114-15			
ANGEL Easy Beige 8114-13 ANGEL Long Beige 8114-14	ANGEL Flexi	Beige	8114-11
ANGEL Long Beige 8114-14	ANGEL Evo	Beige	8114-12
3	ANGEL Easy	Beige	8114-13
ANGEL Short Beige 8114-15	ANGEL Long	Beige	8114-14
	ANGEL Short	Beige	8114-15

UPPER MATERIAL:

- Back: PBI® fabric with hydrophobic and oleophobic treatment that can withstand extreme temperatures.
- Palm: Meta-aramid / Para-aramid knit with silicone coating.

REINFORCEMENT:

- The back knuckles are protected against impact by anti-shock foam placed in the inner layers of the glove.
- Ceramic coating increases abrasion protection on both the fingers and the back reinforcement.

INTERMEDIATE LAYERS:

- Insulating layer recycled Aramid non-woven fabric
- Membrane FR membrane Porelle®.

LINING:

Aramid lining.

STANDARDS:

EN 659:2003+A1:2008.



DuPont™, Kevlar® and Nomex® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.



ANGEL 8114

CUFFS:

- Flexi Cuff made of flame retardant fabrics with stable internal springing.
- Evo Cuff made of PBI® with flexible barrier made of non-flammable fabrics.
- Easy Cuff made of PBI®.
- Long Extended cuff made of PBI® fabric and drawstring waistband with velcro closure.
- Short Basic cuff made of Para-Aramid knitting.

OTHER INFORMATION:

- Anatomical cut glove.
- Reflective elements, high-visible meta-aramid
- Carabiner for hanging the gloves to the garment.
- The glove complies with EN 659 even after 40 washing cycles at 60 °C.

Measurement:	Before washing:	After washing:	
Abrasion resistance	4	4	
Blade cut resistence (palm)	5 / TDM Level E	TDM Level E	
Tear resistance	4	3	
Puncture resistance	3	3	
Burning behaviour	4	4	
Convection heat resistance	4	4	
Radiant heat resistance	2	2	
Contact heat resistance	2	2	
Dexterity	5	3	

SIZES ASSORTMENT:

cm	12,7-15,2	15,2-16,5	16,5 - 19	19 - 21,6	21,6 - 24,2	24,2 - 26,7	26,7 - 29,2	29,2 - 30,4	30,4-32,9
size	5 (XXS)	6 (XS)	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)	13 (4XL)

CARE & MAINTENANCE:

Choose a more ecological short washing program at 40 °C. Wash at a maximum temperature of 60 °C if you need to disinfect the gloves or they are extremely dirty.











PROCEDURE: Remove coarse dirt after each use. Before washing, fasten the Velcro fasteners and remove the snaps. Use a liquid detergent. Wash on a short programme. TO MAKE THE GLOVE FIT BETTER: Shape the glove several times after washing and during drying. Do not dry in direct sunlight or heat sources, do not use a tumble dryer. Store the gloves in a dry environment.

RECOMMENDED USE:

Holík Washing Gel

The washing gel is natural based for leather and textile gloves with high washing efficiency. It reduces bacteria, does not pollute the environment and is fully biodegradable (Eco-Friendly).



Impregnation spray Holík

A highly effective impregnating spray for leather and textiles that protects against moisture, water, oil and dirt while maintaining the breathability of the material. Apply the impregnation in a thin layer on dry product and allow to dry for at least 12 hours.

For more about Washing & Maintenance, visit:

www.holik-international.com > Technologies > Care&Maintenance









Co-funded by the European Union

Holík International, s.r.o.

E-mail: info@holik-international.cz Facebook: holikinternational

Holík GmbH

Von-der-Goltz Strasse 24 DE-42329 Wuppertal, DE Tel.: +49 (0) 202 786 6278 Mob.: +49 170 788 8432 E-mail: mail@holik-gmbh.de Web: www.holik-ambh.de

Holík America, LLC

532 N Regional Rd, Ste A Greensboro, NC 27409, USA Cell: +1 631-636-9212 Office: +1 336-907-8001 E-mail: kolar@holik-international.com

Web: www.holik-america.com

