

# ZLIN GII CH 7125-21 (22)

The new generation of the COMFORT LINE model Zlin with cut protection Level 2. The entire GII line features a unique sole with a sophisticated self-cleaning tread and durability, made of highly durable cowhide leather with hydrophobic treatment. Available with PU or PTFE membrane.

## PRODUCT DESCRIPTION

**Colour:** Black 

**Membrane:** PU B7125-21  
PTFE B7125-22

### UPPER MATERIAL:

- Cowhide leather 2,4–2,6 mm with hydrophobic treatment.
- Ankle protectors.
- TPU toe and heel protection.
- Composite toe cap.
- Inner cushioning made of soft foam material.
- Flexible segmentation in the heel area.
- Reflective elements.
- Combined **footwear fastening** – front lacing for adjusting the shoe width with a locking mechanism at the flexion area of the instep, and a side zipper for quick one-handed fastening.
- Anti-cut reinforcement – Level 2.

### SOLE:

- EXPLORER rubber sole.
- Self-cleaning design.
- Zones with special profiles.
- Anti-static, non-slip, resistant to oils, acids, fuels.
- Heat resistant to 250 °C.
- Shock absorber – in the heel area of the sole to cushion impacts while walking.

### ANTIPERFORATION INSOLE:

- Composite textile with a puncture-resistant plate.

### REMOVABLE INNER SOLE:

- Anatomical, anti-static.
- Insole can be inserted for up to 3 foot widths.

### LINING:

- 4-layer with PU membrane.
- Available also with PTFE.



15090



20345



17249



LEVEL 2



DuPont™, Kevlar® a Nomex® jsou ochranné známky nebo registrované ochranné známky společnosti E.I. du Pont de Nemours and Company.

# ZLIN GII CH 7125-21 (22)

## Shoe features for ZLIN GII CH

F2A	Firefighter's footwear type 2
HI <sub>3</sub>	Heat insulation
SRC	Anti-slip properties
P	Puncture resistance
T	Impact resistance
A	Antistatic footwear
AN	Ankle protection
CI	Cold insulation
HRO	Contact Heat Resistance
FO	Oil resistance
CH	Chainsaw Cut protection Level 2

### TOE CAP:

- Composite – lighter weight than a steel insole. Provides high strength under mechanical stress and impact resistance.

### TOE PROTECTION:

- Anti-kick TPU toe protection.

### HEEL PROTECTION:

- TPU heel protection.

### STANDARDS:

- EN 15090:2012
- ISO 20345:2012
- ISO 17249:2013

### SIZE CHART:

 mm	226	230	240	250	255	260	270	280	285	290	295	300	310	320	325	330
EU	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
UK	3	4	5	6	6,5	7	8	9	9,5	10	11	12	13	14	14,5	15

### MAINTENANCE

Treat dry and cleaned boots with a cream with hydrophobic effect. You can use a suitable waterproofing spray designed for treating membrane boots made of smooth leather. Store the boots dry, cleaned, and treated in a dry and ventilated environment.

### WE RECOMMEND USING:

#### Holík Boot Cream

This product is designed for treating and maintaining membrane's boot in demanding climatic and working conditions. Due to the balanced ratio of hydrophobic ingredients, this cream perfectly treats, softens, and waterproofs membrane boots while maintaining the microclimate inside the boot. It covers very well and significantly revives the colour of the boot. It greases the leather and makes it water-resistant. The treatment cream comes in a practical box with a separate sponge.

#### Holík Waterproofing Spray

A highly effective waterproofing spray for leather and textile. The fluorocarbon-based waterproofing replenishes the water-repellent, oil-repellent, and dirt-repellent treatment while keeping the product breathable. Apply the waterproofing to a cleaned, dry product in a thin layer and let it dry for at least 12 hours.

For more about washing and maintenance, visit:  
[holik-international.com > Technologies > Care&Maintenance](http://holik-international.com > Technologies > Care&Maintenance)



**Co-funded by  
the European Union**

Holík International, s.r.o.  
Za Dvorem 612, Štípa, 763 14 Zlín  
Tel.: +420 577 125 500  
E-mail: [info@holik-international.cz](mailto:info@holik-international.cz)  
Instagram: [holik\\_international](https://www.instagram.com/holik_international)  
Facebook: [holikinternational](https://www.facebook.com/holikinternational)  
Web: [www.holik-international.cz](http://www.holik-international.cz)

Holík GmbH  
Von-der-Goltz Strasse 24  
DE-42329 Wuppertal, DE  
Tel.: +49 (0) 202 786 6278  
Mob.: +49 170 788 8432  
E-mail: [mail@holik-gmbh.de](mailto:mail@holik-gmbh.de)  
Web: [www.holik-gmbh.de](http://www.holik-gmbh.de)

Holík America, LLC  
532 N Regional Rd, Ste A  
Greensboro, NC 27409, USA  
Cell: +1 631-636-9212  
Office: +1 336-907-8001  
E-mail: [kolar@holik-international.com](mailto:kolar@holik-international.com)  
Web: [www.holik-america.com](http://www.holik-america.com)



CE 1023  
6/2025