

SHEILA 8433

Leather gloves with anti-cut protection for the whole hand. Serves against mechanical hazards during all-day activities of police and security forces.

PRODUCT DESCRIPTION

Cuff: Wristlet

Color:  Black

UPPER MATERIAL:

- Goatskin leather with hydrophobic treatment.

LINING:

- PES / Aramid / Glass fiber.

OTHER INFORMATION:

- High strength.
- Increased resistance to mechanical hazards.
- Sensitivity, flexibility.
- Close-fitting comfort fit.
- The wrist part of the glove is tightened with an elastic band.

SIZE ASSORTMENT:

- 7 – 8 – 9 – 10 – 11 – 12



SHEILA Wristlet Black

SHEILA 8433



the wrist part of the glove
is tightened with an
elastic band




sensitivity and flexibility



Increased resistance to
mechanical hazards

SIZE CHART:

 cm	16,5 - 19	19 - 21,6	21,6 - 24,2	24,2 - 26,7	26,7 - 29,2	29,2 - 30,4
size	7 (S)	8 (M)	9 (L)	10 (XL)	11 (2XL)	12 (3XL)

CARE & MAINTENANCE

We recommend hand washing at 35°C.



PROCEDURE: Remove coarse dirt after each use. Before washing, fasten the Velcro fasteners and remove the snaps. Use a liquid detergent. Wash on a short programme. **TO MAKE THE GLOVE FIT BETTER:** Shape the glove several times after washing and during drying. Do not dry in direct sunlight or heat sources, do not use a tumble dryer. Store the gloves in a dry environment.

RECOMMENDED USE:

Holík Washing Gel

The washing gel is natural based for leather and textile gloves with high washing efficiency. It reduces bacteria, does not pollute the environment and is fully biodegradable (Eco-Friendly). Always use rubber protective gloves when hand washing.



Holík Emulsion

The Holík emulsion protects against water, oil, dirt and revives the colour. Adding fat to the leather prevents the leather from hardening during drying. The emulsion is intended as a nourishment for leather products. For easy use, you will also find a sponge in the package for easy application.

Impregnation spray Holík

A highly effective impregnating spray for leather and textiles that protects against moisture, water, oil and dirt while maintaining the breathability of the material. Apply the impregnation in a thin layer on dry product and allow to dry for at least 12 hours.

For more about Care & Maintenance, visit:

www.holik-international.com > [Technologies](#) > [Care & Maintenance](#)



Co-funded by
the European Union

