

ZLIN GII B7125

New model from the COMFORT LINE generation, model Zlin. The whole GII line is distinguished by a unique sole with a sophisticated self-cleaning tread, durability and an auxiliary grip with an extra durable cowhide leather with hydrophobic treatment.



ZLIN GII





STANDARDS:

EN 15090:2012 (EN 15090:2012) EN ISO 20345:2012 (EN ISO 20345:2011)

PRODUCT DESCRIPTION

Colour: Black + Neon Yellow Membrane: PU B7125-01

PTFE B7125-02

UPPER MATERIAL:

- Cowhide leather 2,4–2,6 mm with hydrophobic treatment.
- Ankle protectors.
- TPU toe and heel protection.
- Composite toe cap.
- Inner cushioning made of soft foam material.
- Flexible segmentation in the heel area.
- Reflective elements.
- Combined footwear fastening front lacing for adjusting the shoe width with a locking mechanism at the flexion area of the instep, and a side zipper for quick one-handed fastening.

SOLE:

- EXPLORER rubber sole.
- Self-cleaning design.
- Zones with special profiles.
- Anti-static, non-slip, resistant to oils, acids, fuels.
- Heat resistant to 250 °C.
- Shock absorber in the heel area of the sole to cushion impacts while walking.

ANTIPERFORATION INSOLE:

• Composite textile with a puncture-resistant plate.

REMOVABLE INNER SOLE:

- Anatomical, anti-static.
- Insole can be inserted for up to 3 foot widths.

LINING:

- 4-layer with PU membrane.
- Available also with PTFE.

TOE CAP:

Composite – lighter weight than a steel insole.
Provides high strength under mechanical stress and impact resistance.



ZLIN GII B7125

Shoe features for ZLIN GII										
F2A	Firefighter's footwear type 2									
HI ₃	Heat insulation									
SRC	Anti-slip properties									
Р	Puncture resistance									
Т	Impact resistance									
Α	Antistatic footwear									
AN	Ankle protection									
CI	Cold insulation									
HRO	Contact Heat Resistance									
FO	Oil resistance									

TOE PROTECTION:

• Anti-kick TPU toe protection.

HEEL PROTECTION:

TPU heel protection.

SIZE CHART:

mm	226	230	240	250	255	260	270	280	285	290	295	300	310	320	325	330
EU	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
UK	3	4	5	6	6,5	7	8	9	9,5	10	11	12	13	14	14,5	15

DuPont™, Kevlar® and Nomex® are trademarks or registered trademarks of E.I. du Pont de Nemours and Company.

MAINTENANCE

Treat dry and cleaned boots with a cream with hydrophobic effect. You can use a suitable waterproofing spray designed for treating membrane boots made of smooth leather. Store the boots dry, cleaned, and treated in a dry and ventilated environment.

WE RECOMMEND USING:

Holík Boot Cream

This product is designed for treating and maintaining membrane's boot in demanding climatic and working conditions. Due to the balanced ratio of hydrophobic ingredients, this cream perfectly treats, softens, and waterproofs membrane boots while maintaining the microclimate inside the boot. It covers very well and significantly revives the colour of the boot. It greases the leather and makes it water-resistant. The treatment cream comes in a practical box with a separate sponge.

Holík Waterproofing Spray

A highly effective waterproofing spray for leather and textile. The fluorocarbon-based waterproofing replenishes the water-repellent, oil-repellent, and dirt-repellent treatment while keeping the product breathable. Apply the waterproofing to a cleaned, dry product in a thin layer and let it dry for at least 12 hours.

For more about washing and maintenance, visit: holik-international.com > Technologies > Care&Maintenance









Holík International, s.r.o.

Za Dvorem 612, Štípa, 763 14 Zlín Tel.: +420 577 125 500 E-mail: info@holik-international.cz Instagram: holik_international Facebook: holikinternational Web: www.holik-international.cz

Holík GmbH

Von-der-Goltz Strasse 24 DE-42329 Wuppertal, DE Tel.: +49 (0) 202 786 6278 Mob.: +49 170 788 8432 E-mail: mail@holik-gmbh.de Web: www.holik-gmbh.de

Holík America, LLC

532 N Regional Rd, Ste A Greensboro, NC 27409, USA Cell: +1 631-636-9212 Office: +1 336-907-8001 E-mail: kolar@holik-international.com

Web: <u>www.holik-america.com</u>

